ACE HARDWARE CORP -- KT2 EXTERIOR LATEX HOUSE PAINT - FLAT, 108A100 -- 8010-00N029499

=========== Product Identification ===========

Product ID: KT2 EXTERIOR LATEX HOUSE PAINT - FLAT, 108A100

MSDS Date: 08/20/1991

FSC:8010

NIIN:00N029499 MSDS Number: CCYFW

=== Responsible Party === Company Name:ACE HARDWARE CORP Address:21901 S CENTRAL AVE

City:MATTESON State:IL

ZIP:60443 Country:US

Info Phone Num:708-720-0600
Emergency Phone Num:708-990-6600

CAGE: ACEHA

=== Contractor Identification === Company Name:ACE HARDWARE CORPORATION Address:21901 SOUTH CENTRAL AVENUE

City:MATTESON State:IL ZIP:60443 Country:US

Phone: 708-720-0600

CAGE: ACEHA

======= Composition/Information on Ingredients ========

Ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 6.9%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST

Ingred Name: NEPHELINE SYENITE

CAS:37244-96-5

Fraction by Wt: 9.2%

OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:ALUMINUM SILICATE

CAS:66402-68-4

Fraction by Wt: 15.6%

OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: SILICA, AMORPHOUS, DIATOMACEOUS EARTH; (DIATOMACEIOUS

SILICA)
CAS:61790-53-2
RTECS #:VV7311000
Fraction by Wt: 2.3%
OSHA PEL:20 MPPCF

ACGIH TLV:10 MG/M3 TDUST

Ingred Name: AMMONIA (SARA 302/313) (CERCLA)

CAS:7664-41-7 RTECS #:B00875000 Fraction by Wt: <0.1%

OSHA PEL:50 PPM

ACGIH TLV:25 PPM; 35 STEL

EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

======= Hazards Identification =============

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITANT TO UPPER RESPIRATORY SYSTEM. CHRONIC PROBLEMS WITH RESPIRATORY SYSTEM MAY BE AGGRAVATED BY EXPOSURE TO VAPORS.

Explanation of Carcinogenicity: NOT RELEVANT

Effects of Overexposure:LIGHTHEADEDNESS AND STAGGERED GAIT.

Medical Cond Aggravated by Exposure: CHRONIC PROBLEMS WITH RESPIRATORY SYSTEM MAY BE AGGRAVATED BY EXPOSURE TO VAPORS.

First Aid:INGEST: CALL MD IMMEDIATELY . INHAL: REMOVE FROM EXPOSURE - RESTORE BREATHING - KEEP WARM AND QUIET. SKIN: WASH FROM SKIN WITH SOAP AND WATER. EYES: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES . GET MEDICAL AID. LAUNDER CONTAMINATEDCLOTHING BEFORE REUSE.

=========== Fire Fighting Measures ===================

Flash Point Method:PMCC

Flash Point:199F,93C

Extinguishing Media: NON-COMBUSTIBLE - FOR DRY SOLIDS USE WATER, FOAM, CARBON DIOXIDE, DRY CHEMICALS.

Fire Fighting Procedures: USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY RUPTURE DUE TO PRESSURE BUILD-UP. CONTENTS MAY SPATTER IF TEMPERATURE EXCEEDS 212F.

====== Accidental Release Measures =============

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: DOL STORAGE CATEGORY 3B. Other Precautions: KEEP OUT OF REACH OF CHILDREN.

====== Exposure Controls/Personal Protection =========

Respiratory Protection: DEVICE APPROVED BY NIOSH.

Ventilation:LOCAL EXHAUST PREFERABLE. MECHANICAL (GENERAL) ACCEPTABLE.

Protective Gloves: IMPERVIOUS GLOVES .

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER .

Work Hygienic Practices: AVOID BREATHING VAPOR OR SPRAY MIST. AVOID CONTACT WITH SKIN OR EYES.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Boiling Pt:B.P. Text:212F,100C

Vapor Density: HVR/AIR

Spec Gravity:1.31 (H*20=1)

Evaporation Rate & Reference:SLOWER/ETHER (BUAC=1)

Solubility in Water: INSOLUBLE

Appearance and Odor: WHITE PIGMENTED LIQUID WITH SLIGHT AMMONIA ODOR.

======= Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
NO HAZARDOUS REACTIONS ARE EXPECTED UNDER NORMAL USE.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE.

======= Disposal Considerations ==============

Waste Disposal Methods: INCNERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.